

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. F-6

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T10S R29E
NW 1/16
S8
1986
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 6" in the ground and raised a mound of stone and and earth around the pipe.

From Which:

A Pine 10" dia., Bears N60°26'W., 45.0 ft., scribed: NW 1/16 S8 BT

A Pine 13" dia., Bears N65°14'E., 27.0 ft., scribed: NW 1/16 S8 BT

Measurements to trees taken with an Electronic Tacheometer, with angles turned from the survey control network.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, approx. 40 ft. South & 12 ft. East from the cor.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

**OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848**

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: April 28, 1986
Refer to Map of Survey No. 931

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 27 day of June, 1986
Robert D. Smith by _____
(COUNTY OFFICIAL) (DEPUTY)