

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. G-10

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T10S R29E
W1/16
C--C
S9
1986
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 20" in the ground.
From Which.
A Pine 12" dia., Bears S12°E., 16.3 ft., scribed: C-W 1/16 S9 BT
A Fir 10" dia., Bears S59°W., 13.0 ft., scribed: C-W 1/16 S9 BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, South 3 ft., and East 5 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1969
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: April 16, 1986
Refer to Map of Survey No. 931

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*..... I hereby certify that the within instrument was filed in this office
for record on the.....*20*..... day of.....*June*....., 19.....*86*.....
Robert D. Smith by.....
(COUNTY OFFICIAL) (DEPUTY)