

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. G-13

History of original corner establishment:

Corner is originally established by
Bamford Robb, in 1881, under "General
Land Office" Contract No. 383.
Surveyor Generals Notes State:
Set basalt stone 15x8x7 in mound
of stone for 1/4 Sec. Cor.

DIAGRAM
T10S R29E
1/4
S9.S10
1
1986
PLS 848

Description of corner evidence found:

No evidence of the original stone is found

No accessories originally established.

Corner is lost to old logging.

Established Corner position at proportionate measure
between the Section Corner found 1/2 mi. South and
the Section Corner as established by proportionate
measure, as shown on map of Survey No 931 of the Grant
County Survey Records, 1/2 mi. North.

**Description of monument and accessories | established to perpetuate the
original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 14" in the ground and raised a mound of stone &
earth around the pipe.

From Which:

A Juniper 7" dia., Bears S50°E., 40.1 ft., scribed: 1/4 S10 BT

A Forked Pine 12" dia., Bears S47°W., 57.0 ft., scribed: 1/4 S9 BT

Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence post with
warning Sign, North 5 ft. from the Corner.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

OREGON
JULY 12, 1908
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: April 14, 1986
Refer to Map of Survey No. 931

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 27 day of June, 1986
Robert D. Bissett by _____
(COUNTY OFFICIAL) (DEPUTY)