

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. H-15

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T10S R29E
C
S1/16IS10
C
1986
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 20" in the ground and placed a circle of stone filled with earth around the pipe.

From Which:

A Juniper 6" dia., Bears N47°E., 40.7 ft., scribed: C-S 1/16 S10 BT

Set a 5/8"x30" iron pin with plastic cap, stamped: SURVEY MARKER PLS 848 and steel guard post with Bearing tree & Warning sign, West 4.8 ft.

Measurements to accessories taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of tree. Painted a 6" red band at breast ht. around tree. Set steel fence post with warning & Boundary Signs, South 4 ft. from the corner.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: April 18, 1986
Refer to Map of Survey No. 931

Office of Sumner County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 20 day of June, 1986
Robert D. Safford by _____
(COUNTY OFFICIAL) (DEPUTY)