

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. J-16

History of original corner establishment:

Corner not previously established.

DIAGRAM

T108 R29E
S10
E1/16--
S15
1984
PLS 848

Description of corner evidence found:

Corner not previously established.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 10" in the ground, and raised a mound of stone and earth around the pipe.

From Which:



A Juniper 7" dia. Bears, S10⁰W., 34.0 ft., scribed: E1/16 S15 BT

A Pine 12" dia. Bears, N26⁰W., 45.7 ft., scribed: E1/16 S10 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, South & East 5 ft. from the corner.

Refer to map of survey No. 874



Work by D.M. Ferguson, PLS 848, Mt. Vernon Ore.
On Oct. 21, 1984

Witnessed by J. David Brinton, PLS 2065

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 22 day of July, 1985
Robert W. Brinton by J. David Brinton
(COUNTY OFFICIAL) (DEPUTY)