

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. J-17

History of original corner establishment:

Corner was originally established in Sept., 1891,
By Bamford Robb, U.S. Deputy Surveyor, under
Contract No. 383. Surveyor General's Notes State:
Set basalt stone 16x9x8 in mound of stone for
cor. to secs. 10, 11, 14 & 15 from which
A Pine 14 in. dia. bears S80°E., 32 lks.
" " 12 " " " N16°W., 70 lks.

DIAGRAM

T10S R29E
S10|S11
-.-
S15|S14
1984
PLS 848

Description of corner evidence found:

Found a 12"x7"x7" with no marks apparently visible
lying loose approx. 7 ft. west from an old stone mound.

Found a rotten pine stump with BT scribing visible,
facing the stone mound. There is approx. 8 deg. local
attraction in this area. When using compass reading of
record S16E., 46.2 ft. from the stump, places a point
on the old mound of stone. Therefore accepted the said
point in the stone mound as the section corner position.

Description of monument and accessories | established to perpetuate the
original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 20" in the ground, and raised a mound of stone and
earth around the pipe.

From Which:

A Fir 14" dia. Bears N56°W., 9.8 ft., scribed: T10S R29E S10 BT

A Fir 7" dia. Bears N34°E., 51.2 ft., scribed: T10S R29E S11 BT

A Fir 9" dia. Bears S 9°E., 28.3 ft., scribed: T10S R29E S14 BT

A Juniper 9" dia. Bears S75°W., 52.6 ft., scribed: T10S R29E S15 BT

Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 4" red band at breast ht. around each tree. Set steel fence posts with
warning & Boundary Signs, East & West 3 ft. from the corner.

Refer to map of survey No. 874

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Work by D.M. Ferguson, PLS 848, Mt. Vernon Ore.
On Oct. 21, 1984

Witnessed by J. David Brinton, PLS 2065

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*22*..... day of.....*July*....., 1985
Robert H. Bantz by.....
(COUNTY OFFICIAL) (DEPUTY)