


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. K-15

History of original corner establishment:

Corner not previously established.




Description of corner evidence found:

Corner not previously established.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 10" in the ground, and raised a mound of stone & earth around the pipe.
From Which:
A Fir 14" dia. Bears N68°W., 34.1 ft., scribed: C-N 1/16 S15 BT
A Juniper 4" dia. Bears S55°E., 27.0 ft., scribed: C-N 1/16 S15 BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, East & West 3 ft. from the corner.

Refer to map of survey No. 874



Work by D.M. Ferguson, PLS 848, Mt. Vernon Ore.
On Oct. 22, 1984
Witnessed by J. David Brinton, PLS 2065

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*.....
for record on the.....*22*..... day of.....*July*....., 19.....*85*.....
by.....*Douglas M. Ferguson*..... (COUNTY OFFICIAL) by..... (DEPUTY)