

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. 0-7

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T10S R29E
C
N1/16 S20
C
1986
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 26" in the ground.

From Which.

A Pine 8" dia., Bears N15°W., 24.0 ft., scribed: C-N 1/16 S20 BT

A Pine 8" dia., Bears S36°E., 14.4 ft., scribed: C-N 1/16 S20 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, South 2-1/2 ft. & West 2-1/2 ft. from the Cor.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1999
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: March 26, 1986
Refer to Map of Survey No. 927

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 20 day of June, 1986
Robert D. Bager by _____
(COUNTY OFFICIAL) (DEPUTY)