

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. P-15

History of original corner establishment:

Corner not previously established.

DIAGRAM
PIPE R29E
C1/4
S22
1984
PLS 848

Description of corner evidence found:

Corner not previously established.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 6" in the ground, and raised a mound of stone and earth around the pipe to the top of the cap.
From Which.


A Pine 9" dia. Bears, S32°W., 36.8 ft. scribed, C1/4 S22 BT

A Pine 10" dia. Bears, S70°E., 55.3 ft. scribed, C1/4 S22 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence post with warning & Boundary Sign, in stone mound North alongside corner pipe.

Refer to map of survey No. 874



Work by D.M. Ferguson, PLS 848, Mt. Vernon Ore.
On Oct. 12, 1984
Witnessed by J. David Brinton, PLS 2065

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., hereby certify that the within instrument was filed in this office
for record on the.....*22*..... day of.....*July*....., 19.....*85*.....
.....*[Signature]*..... by.....*[Signature]*.....
(COUNTY OFFICIAL) (DEPUTY)