

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No Q-13

History of original corner establishment:

Corner not previously established.

DIAGRAM

T10S R29E
S1/16
|
S21, S22
|
1984
PLS 848


Description of corner evidence found:

Corner not previously established.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 30" in the ground.
From Which.
A Juniper, 14" dia. Bears S34° 25'W., 22.8 ft., scribed: S1/16 S21 BT
A Juniper, 11" dia. Bears S25° 45'E., 87.2 ft., scribed: S1/16 S22 BT
Measurements to trees taken with total station electronic equipment, turning angle from controle traverse to trees.
Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 4" red band at breast ht. around each tree. Set a steel fence posts with warning & Sign, North 4 ft. Set boundary posts where line crosses Road R/W approx. 250 ft. north and 40 ft. east. from corner.

Refer to map of survey No. 874



OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Work by D.M. Ferguson, PLS 848, Mt. Vernon Ore.
On Oct. 10, 1984
Witnessed by J. David Brinton, PLS 2065

Office of Surveyor County of Grant
State of Oregon hereby certify that the within instrument was filed in this office
for record on the 22 day of July, 1985
Edward D. Brinton by _____
(COUNTY OFFICIAL) (DEPUTY)