

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. R-7

History of original corner establishment:

Corner is originally established by
Bamford Robb, in 1881, under "General
Land Office" Contract No. 383.
Surveyor Generals Notes State:
Set basalt stone 14x12x7 for
1/4 Sec. Cor.

DIAGRAM

T10S R29E
S20
1/4-.-
S29
1986
PLS 848

from which

A pine 18 in dia. bears N40°E., 4 lks. dist.
" " 22 " " " S14°E 55 " "

Description of corner evidence found:

Found 12"x9"x5" stone, set in the ground with "1/4"
on North face.

From Which:

Found 22" Pine, live, in good condition, with scribe
burned out, bears, N56°E., 2.9 ft.
(Record=N40°E., 2.6 ft.)

Found a 22" Pine stump, with scirbing reads 1/4 S BT,
bears, S12°E., 36.5 ft., (Record=S14°E., 36.3)

Since the above described stone looks like it is in its
original position & the bearing trees conform
reasonably well with record, the said stone is accepted
as the 1/4 Sec. Cor. position.

**Description of monument and accessories | established to perpetuate the
original location of this corner:**

Set 2" galvanized iron pipe with 2" Brass Cap, stamped as shown
on the **DIAGRAM**, SET 24" in the ground, set original stone alongside.
From Which.

A Pine 8" dia., Bears N17°E., 28.0 ft., scribed: 1/4 S20 BT

A Pine 10" dia., Bears S61°E., 36.0 ft., scribed: 1/4 S29 BT

Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT. scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence posts with
warning & Boundary Signs, East approx. 15 ft., & West 5 ft. from the cor.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: March 28, 1986
Refer to Map of Survey No. 927

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*20*..... day of.....*June*....., 19.....*86*.....
.....*Robert D. Sager*..... by.....
(COUNTY OFFICIAL) (DEPUTY)