

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. R-8

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T10S R29E
S20
E1/16-.
S29
1986
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 14" in the ground, and raised a mound of stone & earth around the pipe.

From Which:

A Pine 8" dia., Bears N38°E., 24.2 ft., scribed: E1/16 S20 BT

A Juniper 7" dia., Bears S13°W., 42.0 ft., scribed: E1/16 S29 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, North 2.5 ft. & West 2.5 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1980
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: March 28, 1986
Refer to Map of Survey No. 927

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*20* day of.....*June*....., 19.....*86*
.....*Rolene D. Day*..... by.....
(COUNTY OFFICIAL) (DEPUTY)