

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. R-9

History of original corner establishment:

Corner was originally established in Sept., 1881,
By Bamford Robb, U.S. Deputy Surveyor, under
Contract No. 383. Surveyor Generals Notes State:
Set a basalt stone 16x7x6 for cor to sec.
20, 21, 28, 29, from which:
A pine 8 ins dia. bears N76°E., 121 lks dist.
" " 36 " " " N40°W., 182 " "
" " 12 " " " S14°W., 58 " "
" " 20 " " " S42°E., 54 " "

DIAGRAM

T10S R29E
S201S21
-.-
S291S28
1984
PLS 848

Description of corner evidence found:

Found 12"x7"x3" stone, with no marks apparently
visible, set in an old mound of stone. All appear
to be original.

From which:

Found a 36" Pine stump, with scribing reads 29 BT,
Bears, N43°W., 122.2 ft. (Record N40°W., 120.1 ft.)
Found a 24" Pine, live, with scribing, reads, T10S R29E
S29 BT, Bears, Record (S14°W., 38.3 ft.)
Found 24" Pine stump, with scribing, reads, BT
Bears, Record (S42°E., 35.6 ft.)
Found a 12" Pine, live, with scribing reads, 29S
Bears, Record N76°E., 79.9 ft.

Accepted position of the above described stone, as Cor.
Description of monument and accessories established to perpetuate the

original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 6" in the ground, set original stone alongside pipe
and raised a mound of stone around the pipe.

From Which:

A Juniper 6" dia. Bears N74°W., 51.8 ft. scribed S20 BT (tree too small for scri
A Juniper 7" dia. Bears N57°E., 48.3 ft. scribed T10S R29E S21 BT
A Pine 13" dia. Bears S14°E., 42.7 ft. scribed T10S R29E S28 BT
A Juniper 7" dia. Bears S 9°W., 28.5 ft. scribed T10S R29E S29 BT
Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence post with
warning & Boundary Signs, in the stone mound, alongside and north from cor.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Refer to map of survey No. 874

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Work by D.M. Ferguson, PLS 848, Mt. Vernon Ore.
On Oct. 10, 1984
Witnessed by J. David Brinton, PLS 2065

Office of.....*Surveyor*..... County of.....*Giant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*23*..... day of.....*July*....., 19.....*85*.....
.....*Robert A. Brinton*..... by.....
(COUNTY OFFICIAL) (DEPUTY)