


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by W.H. Byars under General
Land Office Contract No. 197 dated July 14, 1873.

Surveyor General's records state:

Set a volcanic stone 14x12x8 for quarter section
corner.



Description of corner evidence found:

At assumed corner location, found a basaltic stone 17" X 12" X 8"
set 8" in ground in well sodded stone mound of 4 stones, marked
"1/4" on west face. Found a 5/8" X 48" long iron rod not of record
driven in alongside original marked stone.

Description of monument and accessories | established to perpetuate the
original location of this corner:

As evidence in vicinity of corner agrees with GLO
original record, at the location of the original
marked stone, set a 30" long 2 1/2" O.D. aluminum
pipe 20" in ground to bedrock with 3 1/4" aluminum
cap marked as shown:

Marked new bearing trees:



A Juniper, 7" DBH, bears South 59° East, 23.5 feet,
scribed "1/4 S30 BT";
A Ponderosa Pine, 12" DBH, bears South 37° west, 43.4 feet,
scribed "1/4 S25 BT".
Raised stone and earth mound 3 feet base to cap and
buried original stone south of cap. Painted 6" red band
and faces red and nailed brass washer stamped "LS 1026"
and signs 54-3 and 54-4 on bearing trees. Set steel
post with sign 54-4 north of cap.

I hereby certify the above corner monument was re-established
as herein described on July 10, 1981.

Witnesses: William S. DeGroot
William S. DeGroot, LS 1633

Shelby H. Griggs
Shelby H. Griggs, Chainman

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 1st day of Oct, 1981
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)



David B. Armstrong
9/21/81 OREGON
AUGUST 22, 1975
DAVID B. ARMSTRONG
1026