


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. 0-1

History of original corner establishment:

Grant County Survey Records show no previous establishment of this corner.



Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 25" in the ground.
From Which.

A Fir 8" dia. Bears, N75°W., 35.4 ft., scribed: N1/16 S24 BT

A Fir 6" dia. Bears, N24°E., 5.8 ft., scribed: N1/16 S19 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted

6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, North & East 5 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Nov. 6, 1984
Refer to Map of Survey No. 908

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*..... I hereby certify that the within instrument was filed in this office
for record on the.....*15* day of.....*May*....., 19..*86*..
Robert W. Ferguson
(COUNTY OFFICIAL) (DEPUTY)