

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

C-N-SE 1/64 S19

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T10S R30E
C-N-SE
1/64
S19
1985
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 24" in the ground.

From Which.

A Pine 15" dia., Bears N64°E., 10.4 ft., scribed: C-N-SE 1/64 S19 BT

A Pine 10" dia., Bears S 6°W., 42.7 ft., scribed: C-N-SE 1/64 S19 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, South & West 6 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Aug. 1, 1985
Refer to Map of Survey No. 908

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*..... hereby certify that the within instrument was filed in this office
for record on the.....*15th* day of.....*Mar*....., 19.....*86*
.....*Robert A. Ferguson*.....
(COUNTY OFFICIAL) (DEPUTY)