

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. P-2

History of original corner establishment:

Grant County Survey Records show no previous establishment of this corner.

DIAGRAM

T10S R30E
W 1/16
C--C
S19
1984
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 26" in the ground.
From Which.
A Fir 13" dia., Bears S17⁰W., 3.3 ft., scribed: C-W 1/16 S19 BT
A Pine 7" dia., Bears N 4⁰E., 30.0 ft., scribed: C-W 1/16 S19 BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence post with warning Sign, East 5 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Oct. 18, 1984
Refer to Map of Survey No. 908

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 17 day of Mar, 1986
Robert D. Bapts by _____
(COUNTY OFFICIAL) (DEPUTY)