

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. P-4

History of original corner establishment:

Grant County Survey Records show no previous establishment of this Cor.

DIAGRAM

T10S R30E
E1/16
C--C
S19
1984
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 28" in the ground.
From Which.

A Fir 8" dia. Bears, N46°W., 7.0 ft. scribed: C-E 1/16 S19 BT

A Fir 12" dia. Bears, S64°W., 7.0 ft. scribed: C-E 1/16 S19 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence post with warning Boundary Sign, north 5 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Oct. 17, 1984
Refer to Map of Survey No. 908

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 17 day of Mar, 1986
by Douglas M. Ferguson (DEPUTY)
(COUNTY OFFICIAL)