

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally set by Henry W. Cook,  
Deputy U. S. Surveyor under Contract 589  
Dated 1891.

Original Notes: Set a Basalt stone 18x10x10 ins.  
12 ins. in ground for 1/4 corners marked 1/4  
on W. face from which:

A Pine 36 ins. dia. bears S48°<sup>(25.7)</sup>W 39 lks. dist.  
marked "1/4 S BT".  
A Pine 25 ins. dia. bears N87°<sup>(40.3)</sup>E 61 lks. dist. marked "1/4 S BT".

Existing mound set by Martin E. Lowther as shown on recovery  
notes dated 8-19-62.

Description of corner evidence found:

There is evidence (hole and mound) just to East of corner location  
that this area was dozed over in the past. Original stone not found.  
Note: Set mon. by record bearing & dist. from Sec. 20 BT. Meas.  
from Ctr. of tree.  
Found 26" Ponderosa Pine. Orig. BT scribed "1/4 S". Bears N87°00'E 40.3 ft.  
Found 30" Pine blowdown stump. Orig. BT face in on underside  
of stump - not opened. Bears S48°00'W 23.6 ft. to tag on end of stump.  
Found 15"x12"x7" stone in stone mound apparently set by Martin  
Lowthery. Stone was N67°00'W, 2.0 ft. from corner location.

**DIAGRAM**

T10S R30E  
1/4 S19 S20

Description of monument and accessories | established to perpetuate the

original location of this corner: Set 30" x 3" aluminum monument with 3" aluminum cap  
& magnet in bottom. Buried stone--apparently not original on south  
side of Mon. Set Mon. by record bearing and distance from Section  
20 BT. Buildt Stone mound around corner.

New bearing trees: New section 20 BT: Marked 11"  
Ponderosa Pine. Bears S49°30'E, 31.72 ft. with  
double axe face. Scribed "1/4 S 20 BT". Tagged  
with brass washer marked "LS 981". New Section  
19BT: Marked 19" Ponderosa Pine. Bears S71°  
00'W, 40.1 ft. with double axe face. Scribed  
"1/4 S 19 BT". Tagged with brass washer marked  
"LS 981".

T10S R30E  
1/4  
S19 S20  
1979  
PLS 981

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*H. Leon Kennedy*

OREGON  
JULY 14, 1972  
H. LEON KENNEDY  
981

I hereby certify the above corner monument  
was re-establishing as herein described  
on November 7, 1979.

H. LEON KENNEDY, P.L.S.  
Witness: /s/ Jeff Clark

Office of Surveyor County of Grant  
State of Oregon, I hereby certify that the within instrument was filed in this office  
for record on the 31 day of Oct, 1980  
Robert D. Baggett  
(COUNTY OFFICIAL) (DEPUTY)