


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by Henry W. Cooke under contract number 589 dated November 10, 1891.

The government field notes state: Set a basalt stone 16x10x10 ins 11 ins in ground for 1/4 Sec. Cor. marked 1/4 on W face from which a pine 16 ins. bears S 89° E 45 L dist marked 1/4 S.B.T. No other trees within limits. Dug pit 18x18x12 5 1/2 ft north of cor and raised a mound of earth alongside.



No record of subsequent remonumentation found in county records.

Description of corner evidence found:

A stone 16 "x10 "x10" 11 ins in ground. I was unable to find any marks on this stone.

From which:

A 30" DBH ponderosa pine Bears S 89° E 45 lks Scribing is visible.

This tree ring growth counts to 1892, the year the original survey was executed.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with 3-1/4" cap marked:

24 "in ground & erected a mound of stones around it. I buried the original stone monument face down, top to N, on the North side of the new monument.

U.S. DEPT.
OF AGRICULTURE
UNLAWFUL TO DISTURB
T10S R30E
1/4
S21 | S22
OPLS 1805
1980
CADASTRAL SURVEY
FOREST SERVICE

from which I scribe a NEW BEARING TREE:

A 17" DBH ponderosa pine Bears N 27° W 23 lks, scribed 1/4 S 21 BT.

Painted faces on BT's red & attached BT & Attention tags.

Used steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT.

This corner was set April 1, 1980.

Office of County Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed
in this office for record on the 22 day of April, 1980
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)

