

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally set by Henry W. Cook Deputy
U. S. Surveyor under Contract 589 Dated 1891.

Original Notes: Set a Basalt stone 18x12x5 ins.
12 ins. in ground for cor. to secs. 20, 21, 28 & 29
marked with 2 notches on south & 4 notches on east
edges from which:

A Pine 16 ins. diam. bears N66°E, 117 lks. dist. marked
T10S R30E S21 BT. A Pine 24 ins. dia. bears S27°E, 81
lks. dist. marked T10S R30E S28 BT. A Pine 38 ins. dia.
bears S40°W, 91 lks. dist. marked T10S R30E S29 BT. A
Pine 40 ins. dia. bears N43°W, 45 lks. dist. marked
T10S R30E S20BT.

DIAGRAM

T10S R30E

S 20	S 21
S 29	S 28

Description of corner evidence found:

At assumed corner location, I found 18"x15"x6" orig. stone with
4 notches on East edge. (Could not find 2 notches on South) Found
1/2" x 36" Iron Rod along East side of rock.

Found 40" split Ponderosa Pine stump with orig. scribing. Bears
N39°30'W 28.7 ft.

Found 24" Ponderosa Pine (healthy tree) with partly open face w/
visible scribes. Bears N 66°30'E 78.8).

Found 24" Ponderosa Pine stump. No visible face or scribes (cut
Low). Bears S5°30'W 59.1 ft.)

Found 21" Ponderosa Pine snag (30' high) with partly open face &
visible scribes. Bears S24 00'E 53.5 ft.)

Description of monument and accessories | established to perpetuate the
original location of this corner:

As evidence in vicinity of corner agrees
with the G.L.O. original record, I set a 2½" x 30" aluminum
monument with a 3½" aluminum cap, and with a magnet in the
bottom. Buried original stone on south side of monument and
built stone mound around monument.

New bearing trees: New Section 29 BT: Marked 10"

Juniper School marm with upper and lower axe face.

Bears S53°00'W, 8.8 ft. Scribed T10S R30E S29 BT".

Tagged with brass washer marked "LS 981".

New Section 28 BT: Marked 9" Ponderosa Pine with upper

and lower axe face. Bears S57°00'E, 44.8 ft. Scribed

"T10S R30E S28 BT". Tagged with brass washer marked

"L.S. 981".

T10S R30E

S20 | S21

S29 | S28

1979

PLS 981

I hereby certify the above corner monument
was re-establishing as herein described
on November 8, 1979.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

H. Leon Kennedy

OREGON
JULY 14, 1972
H. LEON KENNEDY
981

H. LEON KENNEDY, P.L.S.
Witness: /s/ Jeff Clark

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 31 day of Oct, 1980
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)