

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. R-17

History of original corner establishment:

Corner was originally established by, Henry W. Cooke, in 1892, under General Land Office Contract No. 589
Surveyor Generals Notes State:
Set a post 4-1/2 ft long, 4 ins. square with marked stone 24 ins in ground for cor to secs 22 23 26 27 marked T10S S23 on NE, R30E S26 on S & S27 on SW S22 on NW faces, with 2 notches on S and E edges. from which

A Pine 38 ins dia bears N38°E, 49 lks dist marked T10S R30E S23 BT
A Pine 11 ins dia bears S 70°20'E 15 lks dist marked T10S R30E S26 BT
A Pine 28 ins dia bears S89°W, 68 lks dist marked T10S R30E S27 BT
A Pine 12 ins dia bears N34-1/2°W, 32 lks dist marked T10S R30E S22 BT

DIAGRAM

T10S R30E
S22|S23
-.-
S27|S26
1985
PLS 848

Description of corner evidence found:

Found the rotten remains of wood post, no marks visible.

From Which:

Found the remains of all four bearing trees with bits of scirbing visible, at record measurement form the above said post. Accepted post as the Section Corner position.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 27" in the ground.

From Which.

A Fir 8" dia., Bears N67°W., 64.4 ft., scribed: T10S R30E S22 BT

A Fir 8" dia., Bears N76°E., 40.4 ft., scribed: T10S R30E S23 BT

A Pine 22" dia., Bears S32°E., 18.8 ft., scribed: T10S R30E S26 BT

A Fir 12" dia., Bears S48°W., 11.3 ft., scribed: T10S R30E S27 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, East & West 5 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1898
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Aug. 19, 1985
Refer to Map of Survey No. 913

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 12 day of March, 1986
Robert D. Smith by _____
(COUNTY OFFICIAL) (DEPUTY)