

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. S-8

History of original corner establishment:

Grant County Survey Records show no previous establishment of this corner.

DIAGRAM

T10S R30E

NE1/16 S29

1984
PLS 848

Description of corner evidence found:

Grant County Survey Records show no previous establishment of this Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 25" in the ground.
From Which.
A Juniper 8" dia. Bears, N58°W., 8.8 ft., scribed: NE 1/16 S29 BT
A Juniper 8" dia. Bears, S17°E., 12.6 ft., scribed: NE 1/16 S29 BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence posts with warning & Boundary Signs, North & West 5 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Nov. 7, 1985
Refer to Map of Survey No. 908

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 12 day of Mar, 1986
Robert D. Buzitt by _____
(COUNTY OFFICIAL) (DEPUTY)