

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. V-15

History of original corner establishment:

Corner was originally established by,
Henry W. Cooke, in 1892, under
General Land Office Contract No. 589
Surveyor Generals Notes State:
39.88 ch. Set a basalt stone 16x12x10
ins. 11 ins. in ground, for 1/4
sec cor marked 1/4 on N face.

DIAGRAM

T10S R30E
S27
1/4--
S34
1985
PLS 848

from which

A fir 6 ins dia bears N67°E., 15 lks dist marked 1/4 S BT
A fir 4 ins dia bears S38°E., 18 lks dist marked 1/4 S BT

40.40 Brook 8 lks wide runs SW

Description of corner evidence found:

No trace of original stone is found. Search area is refined to a small area by measurements from surrounding evidence and call to the brook. 34 ft. west. A large radius is also searched. No evidence of the original Bearing trees is found, the small white fir probably completely decomposed. The position as determined by proportion falls on the edge of the Brook, therefore, in order to conform to the call for the Brook at 34 ft. West, the corner locus is moved South 25 ft. from the proportioned position. (East West position is determined at proportionate measure from the corners 1/2 mi. East & West and the North South position is set at 25 ft. South from the said proportioned position.)

Note: The call to the Brook could not be disregarded in this case. It is apparent that the measurement along this section line was relatively accurate.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 18" in the ground and raised a mound of stone & earth around the pipe.

From Which:

A Pine 12" dia., Bears N25°W., 13.7 ft., scribed: 1/4 S27 BT

A Fir 8" dia., Bears S58-1/2°E., 28.4 ft., scribed: 1/4 S34 BT

Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence post with warning Sign, North 5 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Aug. 2, 1985
Refer to Map of Survey No. 913

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 12 day of May, 1986
Robert D. Smith by _____
(COUNTY OFFICIAL) (DEPUTY)