

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. V-21

History of original corner establishment:

Corner was originally established by,
Henry W. Cooke, in 1892, under
General Land Office Contract No. 589
Surveyor Generals Notes State:
Set a post 5 ft. long 4 ins square
with a marked stone 24 ins in
ground for cor to secs 25 26 35 36
marked T10S S25 on NE, R30E S36
on SE, S35 on SW, S26 on NW faces
with 1 notch on S and E edges.
From Which

A pine 38 ins dia bears N38°E, 147 lks dist marked T10S R30E S25 BT
A fir 30 ins dia bears S44°E, 172 lks dist marked T10S R30E S36 BT
A pine 4 ins dia bears S27°W, 86 lks dist marked T10S R30E S35 BT
A fir 36 ins dia bears N 5°W, 154 lks dist marked T10S R30E S26 BT

DIAGRAM

T10S R30E
S26 S25
-.-
S35 S36
1985
PLS 848

Description of corner evidence found:

No evidence of the original post and marked stone is found.
Found an old mound of stone with a hub & tack in the center, at a
South & East fence corner.

From Which:

A Pine 37" dia., live in good condition, with scribe visible, Bears
N40°E., 96.8 ft. (Rec.-N38°E., 97.0 ft.) A Fir stump 36" dia., Bears
S43°E., 112.5 ft. (Rec.-S44°E., 113.5 ft.)

A Pine 33" dia., live in good condition with Blaze healed over Bears
S28°W., 57.0 ft. (Rec.-S27°W., 56.8 ft.) A Fir 32" dia., live
in good condition with scribing visible Bears N 1°W., 102.2
ft. (Rec.-N 5°W., 101.6 ft.) Since the stone mound looks original
and the Bearing Trees Conform to record measurement reasonably well
and no better overall position can be found, the center
of the stone mound is accepted as the 1/4 corner locus.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 14" in the ground and raised a mound of stone and
earth around the pipe.

From Which:

The NW, NE & SW original Bearing Trees, being in good condition are not
replaced by new Trees, no new scribing on the original trees.

A Fir 8" dia., Bears S57°E., 111.5 ft., scribed: T10S R30E., S36 BT.
Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence post with
warning Sign, North 4 ft. from the corner. Brass Washer nailed to the
new Bearing tree only.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Aug. 16, 1985
Refer to Map of Survey No. 919

Office of.....*Sumner*..... County of.....*Grant*.....
State of.....*Oregon*..... I hereby certify that the within instrument was filed in this office
for record on the.....*12*..... day of.....*May*....., 19.....*86*
Robert D. Smith.....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

SUPERSEDED BY
Remon Sheet filed
June 20, 1986

V-21