


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. X-13

History of original corner establishment:

Corner was originally established by,
Henry W. Cooke, in 1892, under
General Land Office Contract No. 589
Surveyor Generals Notes State:
Set a basalt stone 20x14x10 ins.
15 ins in ground for 1/4 sec cor.
marked 1/4 on W face.



from which

A pine 30 ins dia. bears N63°W., 37 lks dist marked 1/4 S BT
A pine 30 ins dia. bears N62°E., 32 lks dist marked 1/4 S BT

Description of corner evidence found:

Found 16"x10"x6" stone, set loose in fence line.
Stone is rough, no marks apparently visible.
From Which:
A Pine stump, 30" dia., 6' high, Bears N63°W.,
22.8 ft, scribing, 1/4 S is visible.
(Record N63°W., 24.4 ft.)
A dead & down Pine, 30" dia., with ax marks visible,
bears N62°E., 19.6 ft.
(Record N62°E., 21.1 ft.)
Accepted above described stone as 1/4 Sec. Cor.

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the **DIAGRAM**, SET 26" in the ground and set original stone North alongside pipe.
From Which:
A Pine 10" dia., Bears N69°W., 32.4 ft., scribed: 1/4 S33 BT
A Tamarack 13" dia., Bears S47°E., 20.3 ft., scribed: 1/4 S34 BT
Measurements to trees taken with a metal tape and magnetic compass, with Declination set off 20 deg. East.
Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing Tree Sign above blaze, and warning sign on back of each tree. Painted a 6" red band at breast ht. around each tree. Set steel fence post with warning Sign, North 5 ft. from the corner.



This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Aug. 14, 1985
Refer to Map of Survey No. 913

Office of..... *Sumner* County of..... *Grant*
State of..... *Oregon* I hereby certify that the within instrument was filed in this office
for record on the..... *12* day of..... *May* 19..... *86*
..... *Robert D. Sargent* by
(COUNTY OFFICIAL) (DEPUTY)