

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. X-21

History of original corner establishment:

Corner was originally established by,
Henry W. Cooke, in 1892, under
General Land Office Contract No. 589
Surveyor Generals Notes State:
Set a post 4 ft. long 4 ins square
with a marked stone 24 ins in ground
for 1/4 sec cor marked 1/4 on W face

DIAGRAM

T10S R30E
1/4
S351S36
1985
PLS 848

from which

A pine 24 ins dia. bears N70°E, 33 lks dist marked 1/4 S BT
A pine 42 ins dia. bears S86°W, 86 lks dist marked 1/4 S BT

Description of corner evidence found:

No evidence of the original post or marked stone
is found.

found remains of rotten Pine stump with "BT" scribe
visible on SW face. The other Bearing Tree cannot be
positively identified, therefore the corner position is
established at Record S70°W., 21.8 ft. from the
the above described Pine stump.

**Description of monument and accessories | established to perpetuate the
original location of this corner:**

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown
on the **DIAGRAM**, SET 26" in the ground.
From Which.

A Fir 8" dia., Bears S81°E., 43.9 ft., scribed: 1/4 S36 BT

A Fir 12" dia., Bears S89°W., 21.4 ft., scribed: 1/4 S35 BT

Measurements to trees taken with a metal tape and magnetic compass,
with Declination set off 20 deg. East.

Nailed a brass washer stamped PLS 848 on blaze above BT scribe, Bearing
Tree Sign above blaze, and warning sign on back of each tree. Painted
a 6" red band at breast ht. around each tree. Set steel fence post with
warning Sign, North 5 ft. from the corner.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

This work is performed by:
Douglas M. Ferguson PLS 848
Mt. Vernon Oregon.
On: Aug. 16, 1985
Refer to Map of Survey No. 919

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 12 day of May, 1986
Robert D. Duff by _____
(COUNTY OFFICIAL) (DEPUTY)