

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:  
New Corner

\*

DIAGRAM  
T10S R31E  
SE1/16  
+  
S12

Description of corner evidence found:

Description of monument and accessories I establish to perpetuate the original location of this corner:

Set a 2x28" aluminum monument 9" in the ground in a mound of stone.

I establish new bearing trees:

A 14" P.Pine bears S 36-3/4° W, 70.0 ft, scribed SE1/16S12BT.


A 10" P.Pine bears N 54° W, 112.5 ft, scribed SE1/16S12BT.

T10S R31E  
SE1/16  
+  
S12  
PLS1918  
1988

New BTs have 3/4" brass washers marked PLS1918 attached to the BT blaze, faces and bands painted with red tree marking paint, and BT tags and Attention or Land Survey Monument signs. A steel fence post with Attention or Land Survey Monument sign is driven approximately 3-5 feet from the corner.

Sun Cadastral Survey, Cont No. 53-04H1-7-4011  
Field Book: 4-35  
Work accomplished: 8/22/88  
Witnesses: Louise Parsons, Douglas Parsons  
Job No.: 87221

PARSONS SURVEYING  
1915 S.E. Stone Street  
Corvallis, OR 97333  
(503) 752-7515



Office of COUNTY SURVEYOR County of GRANT  
State of OREGON, I hereby certify that the within instrument was filed in this office  
for record on the 2<sup>nd</sup> day of Feb, 1987

Ronald D. Leggett by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)