


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally set by Rufus S. Moore, Deputy U.S. Surveyor, under his Contract No. 382, dated March 1881.

Original Notes: Set a basalt stone 20x12x3 and raised mound of stone for cor. to Sec. 15, 16, 21, 22.



Description of corner evidence found:


Fd. 18"x14"x3" dome shaped stone (20"x12"x3") at south end of gate. Record calls to rock rim south and east confirm this location.

No bearing trees or other official accessories found.

Description of monument and accessories I established to perpetuate the original location of this corner

At the corner location I set a 2½"x30" aluminum monument with a magnet in the base and a 3½" cap stamped as shown.

An 8" juniper with double ax face brs. N84 E a dist. of 66.3 ft. scribed "T10S R31E S15 BT". Set PK nail in 18"x18"x20" basalt stone brs. N62½ W a dist. of 62.28 ft. Set PK nail in 48"x22"x20" basalt stone brs. S30 W a dist. of 24.25 ft. Set PK nail in 36"x30"x18". NO OTHER TREES AVAILABLE.



All new trees tagged with brass washer "PLS 1632".

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Richard C. Clark

**OREGON
JULY 14, 1978
RICHARD CLARK
1632**

I hereby certify the above corner monument was re-established as herein described on August 12, 1980.

Richard C. Clark, P.L.S.
Witnesses: /s/ J. Clark
L. Kinart

Office of Surveyor County of Grant
State of Oregon I hereby certify that the within instrument was filed in this office
for record on the 31 day of Oct, 1980
Robert O. Bagert by _____
(COUNTY OFFICIAL) (DEPUTY)