


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally set by Rufus S. Moore, Deputy U.S. Surveyor under his contract No. 382, dated March 1881.

Original Notes: Set a basalt stone 18x15x4 and raised a mound of stone for 1/4 sec. cor.



Description of corner evidence found:

Fd. 18"x14"x6" stone (18"x15"x4") in mound of stone at location tagged by E. Calkins 3/21/79.


No bearing trees or other official accessories found.

Description of monument and accessories I established to perpetuate the original location of this corner

At the corner location I set a 2 1/2"x30" aluminum monument with a magnet in the base and a 3 1/2" cap stamped as shown. I bury the original stone on the south side of the monument.

A 13" juniper with double ax face brs. N49 W a dist. of 39.2 ft. scribed "1/4 S22 BT". An 8" juniper with double ax face brs. S87 1/2 E a dist. of 85.0 ft. scribed "1/4 S23 BT".

All new trees tagged with brass washer "PLS 1632".



REGISTERED
PROFESSIONAL
LAND SURVEYOR

Richard Clark

OREGON
JULY 14, 1978
RICHARD CLARK
1632

I hereby certify the above corner monument was re-established as herein described on July 13, 1980.

Richard C. Clark, P.L.S.
Witnesses: /s/ C. Goodwin
J. Clark
L. Kinart

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 31 day of Oct 1980
Robert D. Beget by _____
(COUNTY OFFICIAL) (DEPUTY)