


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally set by Rufus S. Moore, Deputy U.S. Surveyor, under his contract No. 382, dated March 1881.

Original Notes: Set a pine post for 1/4 Sec. Cor. from which a

Tamarack 10 in. in dia. bears N48°W 35 lks dist.
Tamarack 14 in. in dia. bears S58°E 30 lks dist.



Description of corner evidence found:

No corner monument found.

Fd. OBT was 10" now 17" tamarack alive and well brs. N48 W a dist. of 23.1 ft. (48 W 35 lks.)


Fd. OBT was 14" tamarack now dead and down brs. S47 E a dist. of 19.8 ft. to root wad depression. (S53 E 30 lks.)

Description of monument and accessories I established to perpetuate the original location of this corner

At the corner location as established from the original bearing trees I set a 2½"x30" aluminum monument with a magnet in the base and a 3½" cap stamped as shown.

A 10" fir with double ax face brs. S87 E a dist. of 32.4 ft. scribed "1/4 S19 BT".

All new trees tagged with brass washer "PLS 1632".



**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Richard C. Clark

**OREGON
JULY 14, 1978
RICHARD CLARK
1632**

I hereby certify the above corner monument was re-established as herein described on June 20, 1980.

Richard C. Clark, P.L.S.
Witnesses: /s/ J. Clark
L. Kinart

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 31 day of Oct 1980
Robert D. Begett by _____
(COUNTY OFFICIAL) (DEPUTY)