

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: *

The original corner was established by Rufus S. Moore in 1881 under Contract No. 382, dated March 1881.

The original notes state:

North between secs 28 & 29

80.00 Set a basalt stone 14x10x5 and dug pits for cor to secs 20, 21, 28, & 29

DIAGRAM

T10S R31E

S20S21

----+----

S29S28

Description of corner evidence found:

Found a 14x10x5 (14x10x5) stone, 2 notches on the South side, 4 notches on the East side, at the intersection of a North/South fence and a remenant fence East.

Description of monument and accessories I establish to perpetuate the original location of this corner:

Set a 2x28" aluminum monument 16" in the ground in a mound of stone and buried the original stone on the South side.

I establish new bearing trees:

A 16" P.Pine bears N 48⁰ W, 21.5 ft, scribed T10SR31ES20BT.

A 16" P.Pine bears S 62-3/4⁰ W, 34.8 ft, scribed T10SR31ES29BT.

A 15" P.Pine bears S 48-3/4⁰ E, 63.0 ft, scribed T10SR31ES28BT.

An 18" P.Pine bears N 47⁰ E, 10.3 ft, scribed T10SR31ES21BT.

T10S R31E

S20S21

----+----

S29S28

PLS1918

1988

Sun Cadastral Survey, Cont. No. 53-04H1-7-4011

Field Book: 4-72

Work accomplished: 10/15/88

Witnesses: Tyler Parsons, Louise Parsons, Lowell Seaders.

New BTs have 3/4" brass washers marked PLS1918 attached to the BT blaze, faces and bands painted with red tree marking paint, and BT tags and Land Survey Monument signs. A steel fence post with Land Survey Monument sign is driven approximately 3-5 feet from the corner.

PARSONS SURVEYING
1915 S.E. Stone Street
Corvallis, OR 97333
(503) 752-7515

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Tyler B. Parsons

OREGON
JULY 18, 1980
TYLER B. PARSONS
1918

Office of County Surveyor County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 17th day of July, 1987

Lowell Seaders by _____
(COUNTY OFFICIAL) (DEPUTY)