

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:  
None

\*

DIAGRAM  
T10S R31E  
C1/4  
+  
S30

Description of corner evidence found:

Description of monument and accessories I establish to perpetuate the original location of this corner:

Set a 2 1/2"x28" aluminum monument 20" in the ground in a mound of stone.

I establish new bearing trees:

A 7" Fir bears S 33-3/4° E, 29.0 ft, scribed C1/4S30BT.

An 8" Fir bears S 67° W, 40.9 ft, scribed C1/4S30BT.

T10S R31E  
C1/4  
+  
S30  
PLS1918  
1988

Sun Cadastral Survey, Cont. No. 53-04H1-7-4011


Field Book: 7-4

Work accomplished: 10/24/88

Witnesses: Tyler Parsons, Louise Parsons, Lowell Seaders

New BTs have 3/4" brass washers marked PLS1918 attached to the BT blaze, faces and bands painted with red tree marking paint, and BT tags and Land Survey Monument signs. A steel fence post with Land Survey Monument sign is driven approximately 3-5 feet from the corner.

PARSONS SURVEYING  
1915 S.E. Stone Street  
Corvallis, OR 97333  
(503) 752-7515



Office of County Surveyor County of GRANT  
State of OREGON, I hereby certify that the within instrument was filed in this office  
for record on the 7th day of Feb, 1989

Robert D. Baggett by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)