


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

Corner originally set by Rufus S. Moore, Deputy U.S. Surveyor, under his contract No. 382, dated March 1881.

Original Notes: Set basalt stone 16x7x5 for 1/4 sec. cor. from which a

Pine 20 in. in dia. bears S69°W 152 lks. dist.  
Juniper 12" in dia. bears N22°E 29 lks. dist.



**Description of corner evidence found:**


Fd. 15"x11"x17" stone (16"x7"x5").  
Fd. OBT was 12" now 17" juniper alive and well brs. N22 E a dist. of 19.1 ft. (N22 E 29 lks.)  
Fd. OBT was 20" pine now 28" snag brs. S74½W a dist. of 104.0 ft. (S69 W 152 lks.)

**Description of monument and accessories I established to perpetuate the original location of this corner**

At the corner location as determined by the record bearing and distance from the original S30 BT I set a 2½"x30" aluminum monument with a magnet in base and a 3½" cap stamped as shown.

An 18" juniper with double ax face brs. N21 W a dist. of 28.4 ft. scribed "1/4 S25 BT".

All new trees tagged with brass washer "PLS 1632".



**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*Richard Clark*

**OREGON  
JULY 14, 1978  
RICHARD CLARK  
1632**

I hereby certify the above corner monument was re-established as herein described on June 21, 1980.

Richard Clark, P.L.S.  
Witnesses: /s/ J. Clark  
L. Kinart

Office of Surveyor County of Grant  
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 31 day of Oct 80  
Robert D. Boyd by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)