

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: \*

The original corner was established in 1881 by Rufus S. Moore under Contract No. 382.  
The original notes state:  
N89°57' West on a true line bet secs 29&32  
39.97 Set a basalt stone 14x8x4 and dug pits for 1/4 sec cor.

DIAGRAM  
T10S R31E  
S29  
1/4---  
S32

Description of corner evidence found:

Found no evidence of the original corner.

Description of monument and accessories I establish to perpetuate the original location of this corner:


I reestablish this corner by single proportion. Set a 2-1/2"x30" aluminum monument 22" in the ground in a small mound of stone.  
I establish new bearing trees:  
A 9" Juniper bears N 14°32' W, 36.1 ft, scribed 1/4S29BT.  
A 6" Juniper bears S 31°32' E, 30.1 ft, scribed 1/4S32BT.

T10S R31E  
S29  
1/4---  
S32  
PLS1918  
1989

Sun Cadastral Survey  
Contract No.: 53-04H1-7-4011  
Project No.: 8722JB  
Field Book: 7-33  
Work Accomplished: 4/6/89  
Witnesses: Louise Parsons

New BTs have 3/4" brass washers marked PLS1918 attached to the BT blaze, faces and bands painted with red tree marking paint, and BT tags and Attention or Land Survey Monument signs. A steel fence post with Attention or Land Survey Monument sign is driven approximately 3-5 feet from the corner.

PARSONS SURVEYING  
1915 S.E. Stone Street  
Corvallis, OR 97333  
(503) 752-7515



Office of COUNTY SURVEYOR County of GRANT  
State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 26 day of June, 1989

Robert D. Baggett by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)