

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: *

The original corner was established in 1881 by Rufus S. Moore under Contract No. 382.

The original notes state:

80.00 Set a basalt stone 34x8x8 and mound of stone for cor 28,29,32,33.

DIAGRAM

T10S R31E
S29|S28
---+---
S32|S33

Description of corner evidence found:

Found no evidence of the original corner.

Description of monument and accessories I establish to perpetuate the original location of this corner:

I reestablished this corner by double proportion. Set a 2-1/2"x30" aluminum monument 10" in the ground in a mound of stone.

I establish new bearing trees:

A 5" Juniper bears N 35°14' W, 104.0 ft, scribed T10SR31ES29BT.


An 11" Juniper bears S 86°09' E, 17.1 ft, scribed T10SR31ES33BT.

T10S R31E
S29|S28
---+---
S32|S33
PLS1918
1989

Sun Cadastral Survey
Contract No.: 53-04H1-7-4011
Project No.: 8722JB
Field Book: 7-32
Work Accomplished: 4/6/89
Witnesses: Louise Parsons

New BTs have 3/4" brass washers marked PLS1918 attached to the BT blaze, faces and bands painted with red tree marking paint, and BT tags and Attention or Land Survey Monument signs. A steel fence post with Attention or Land Survey Monument sign is driven approximately 3-5 feet from the corner.

PARSONS SURVEYING
1915 S.E. Stone Street
Corvallis, OR 97333
(503) 752-7515



Office of COUNTY SURVEYOR County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 26 day of June, 1989

Robert D. Sargent by _____
(COUNTY OFFICIAL) (DEPUTY)