


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally set by Rufus S. Moore, Deputy U.S. Surveyor, under his Contract No. 382 dated March 1881.

Original Notes: Set a basalt stone 18x18x4 and raised a mound of stone for cor. to Secs. 27, 28, 33 and 34 from which

A Y. Pine 30 in. dia. bears N40°E 14 lks. dist.
A Y. Pine 36 in. dia. bears S74°W 38 lks. dist.



Description of corner evidence found:


End. 18"x12"x10" stone (R: 18"x18"x4") in mound of stone.

End. 30" pine stump brs. N 40°E 9.2 ft. (30" pine N 40°E 14 lks.)
End. 31" pine snag with visible scribing Brs. S 74°W 27.5 ft. (S74°W 38 lks.)

Description of monument and accessories I established to perpetuate the original location of this corner

At the corner location I set a 2½" x30" aluminum monument with magnet in base and a 3½" cap stamped as shown. I use original stone in the mound.

An 8" pine with double ax face brs. N47°W a dist. of 27.8 ft. scribed "T10S R31E S28 BT".
A 9" pine with double ax face brs. N61°E a dist. of 16.8 ft. scribed "T10S R31E S27 BT". A 7" pine with double ax brs. S79½°E a dist. of 26.0 ft. scribed "T10S R31E S34 BT".



No suitable trees in SW Quadrant.
All new trees tagged with brass washer "PLS 1632".



I hereby certify the above corner monument was re-established as herein described on July 10, 1980.

Richard C. Clark, PLS
Witness: /s/ L. Kinart

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 31 day of Oct 1980.
Robert R. Bejert by _____
(COUNTY OFFICIAL) (DEPUTY)