


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally set by Rufus S. Moore, Deputy U. S. Surveyor, under his Contract No. 382 dated March 1881.

Original Notes: Set a fir post for cor. to secs. 26, 27, 34, 35 from which

- A fir 18 in. in dia. bears S58°E 34 lks. dist.
- A pine 6 in. in dia. bears S 60°W 28 lks. dist.
- A fir 6 in. in dia. bears N53°E 11 lks. dist.
- A tamarack 20 in. in dia. bears N35°W 50 lks. dist.



Description of corner evidence found:

No corner monument found.

Fd. OBT was 6" fir now 15" m?L dead, down and decomposed and are unable to determine its exact original location. Fd. OBT was 20" tamarack now 28" alive and well. We open to reveal scribe brs. N35°W a dist. of 33.0 ft. (N35°W 50 lks).

No sign of other BT's.


Description of monument and accessories I established to perpetuate the original location of this corner

At the called bearing and distance from the original NW BT, I set a 2½" x 30" aluminum monument with a magnet in the base and a 3½" cap stamped as shown.

An 8" fir with double ax face brs. S72°E a dist. of 12.2 ft. scribed "T10S R31E S35 BT". A 12" pine with double ax face brs. S5½°E a dist. of 18.8 ft. scribed "T10S R31E S35 BT". A 17" pine with double ax face brs. S 53°W a dist. of 34.3 ft. scribed "T10S R31E S34 BT".

No suitable trees in the NE quadrant.

All new trees tagged with brass washer "PLS 1632".



**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Richard Clark

OREGON
JULY 14, 1978
RICHARD CLARK
1632

I hereby certify the above corner monument was re-established as herein described on July 15, 1980.

Richard C. Clark, P.L.S.
Witnesses: /s/ C. Goodwin
J. Clark
L. Kinart

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 21 day of Oct 1980
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)