

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**


**History of original corner establishment:**

Corner originally set by Rufus S. Moore, Deputy U.S. Surveyor, under his Contract No. 382 dated March 1881.

Original Notes: Set a fir post for 1/4 sec. cor. from which

A tamarack 12 in. dia. bears S 59° E 8 lks.

A Y. Pine 10 in. dia. bears N 28°W 11 lks.



**Description of corner evidence found:**


No corner monument found.

Fd. Original 12" tamarack now 16" snag with visible scribing brs. S59 E a dist. of 5.3 ft. (S59 E 8 lks.)

Fd. original 10" pine now 8" dead and down with visible scribing. Root wad depression brs. N19 W a dist. of 8.0 ft. (N28 W 11 lks.)

**Description of monument and accessories I established to perpetuate the original location of this corner**

At the record bearing and distance from the one original BT still standing, I set a 2½" x 30" aluminum monument with a magnet in the base and a 3½" cap stamped as shown.



A 9" fir with double ax face brs. N54½ W a dist. of 18.0 ft. scribed "1/4 S34 BT". An 18" fir with double ax face brs. S73 E a dist. of 30.5 ft. scribed "1/4 S35 BT".

All new BTs tagged with brass washer stamped "PLS 1632".

I hereby certify the above corner monument was re-established as herein described on September 23, 1980.

**REGISTERED  
PROFESSIONAL  
LAND SURVEYOR**

*Richard Clark*

**OREGON  
JULY 14, 1978  
RICHARD CLARK  
1632**

Richard C. Clark, P.L.S.  
Witness: /s/ L. Kinart

Office of Surveyor County of Grant  
State of Oregon, I hereby certify that the within instrument was filed in this office  
for record on the 31 day of Oct 1980.  
Robert D. Begett by \_\_\_\_\_ (DEPUTY)  
(COUNTY OFFICIAL)