

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


March 22, 1968

History of original corner establishment:

Set post for 1/4 sec. cor. from which

A fir, 10 ins. diam., bears S.45°E., 66 lks. dist.

A fir, 30 ins. diam., bears N.50°E., 37 lks. dist.



Corr. DOB

Description of corner evidence found:

No evidence of the orig. cor. post found.

Found:

A 30 " fir ins. diam. in SE quadrant mkd. 1/4 S.BT.

A 30 " fir stump in NE quadrant, no mks. visible, but at record bearing and distance from cor. position.

Description of monument and accessories I established to perpetuate the original location of this corner At the corner point:

Set a basalt stone 17 x 12 x 11 ins., 8 ins. in the ground, mkd. 1/4 CS on E. face and X on top of stone.

From which

New bearing trees:

A fir, 8 ins. diam., bears S.62°W., 26.0 ft. dist., mkd. 1/4 S3 CS BT

A fir 22 ins. diam., bears N.32°W., 28.5 ft. dist., mkd. 1/4 S34 CS BT.

REGISTERED  
OREGON  
LAND SURVEYOR

*Duane I. Griffith*

JULY 10, 1964  
DUANE I. GRIFFITH  
644

Office of County Clerk County of Grant  
 State of Oregon, I hereby certify that the within instrument was filed in this office  
 for record on the 24 day of March, 1968, at 9 o'clock a.m., (signed)  
John J. Herrera by \_\_\_\_\_  
 (COUNTY OFFICIAL) (DEPUTY)