


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

March 22, 1968

History of original corner establishment:

Set post for $\frac{1}{4}$ sec. cor. from which
A pine, 10 ins. diam., bears N.50°W., 19 lks. dist.
A pine, 12 ins. diam., bears N.65°E., 54 lks. dist.



Description of corner evidence found:

The original cor. monument was a wood post, no evidence of this post was found.

Found one original bearing tree:

A 25" decaying pine stump mkd. BT. in NW quadrant.

Description of monument and accessories I established to perpetuate the original location of this corner

From the stump BT I reverse the record bearing and run S.50°E., 19 lks. to establish the $\frac{1}{4}$ corner.

Set a basalt stone, 16x9x10 inches, 8 inches in the ground, mkd. $\frac{1}{4}$ CS on the E. face and X on top of stone.

from which

New bearing trees:

A pine, 17 ins. diam., bears N.32 $\frac{1}{2}$ °E., 44.5 ft. dist., mkd., $\frac{1}{4}$ S2 CS BT.

A fir, 18 ins. diam., bears S.89°W., 155.0 ft. dist., mkd., $\frac{1}{4}$ S3 CS BT.

REGISTERED
OREGON
LAND SURVEYOR

Duane I. Griffith
JULY 10, 1964
DUANE I. GRIFFITH
644

Office of *County Clerk* County of *Grant*
State of *Oregon*, I hereby certify that the within instrument was filed in this office
for record on the *27* day of *March*, 19*68*, at *9:02* o'clock *a.*m., (signed)
John J. ... by *...*
(COUNTY OFFICIAL) (DEPUTY)