

SEE RECORD

CERTIFIED RECORD OF LAND CORNER MONUMENTATION SURVEY NO 1099

INDEX No. E-6

**History of original corner establishment:**

None. Corner was established as part of this survey.

**DIAGRAM**

T 10 S R 33 E

W 1/16  $\frac{S}{S}$   $\frac{5}{8}$

PLS . 1106

1989

**Description of corner evidence found:**

None...an old location poster on a 18" fir brs N6<sup>0</sup>W, 13' from corner point.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

At position determined by survey... Set a 2½" x 30" aluminum pipe with standard ¾" USDA aluminum cap 24" in ground and surrounded with mound of earth & stone. Cap marked as shown in corner diagram.

New bearing trees established:

A 26" ponderosa pine brs N66½<sup>0</sup>W, 79.5' scribed W 1/16 S5 BT.

A 9" ponderosa pine brs S4½<sup>0</sup>W, 132.5' scribed W 1/16 S8 BT.

New bearing trees have a brass washer stamped PLS 1106 nailed to face of blaze. Attached sign 54-3 & 54-9 to each BT & painted face of blaze & 6" red band around each BT. Set steel fence post North of corner on National Forest Boundary and attached sign 54-9 & 54-2.

Compass declination 18<sup>0</sup> East.

I hereby certify that the above corner was properly established by me to U.S.F.S. standards and witnessed by Bill Quaempts on July 14, 1989.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*William R. Wells*

OREGON  
JULY 22, 1977  
WILLIAM R. WELLS  
1106

Office of.....County Surveyor..... County of.....Grant.....  
State of.....Oregon....., I hereby certify that the within instrument was filed in this office  
for record on the...29... day of...Jan... 19...90  
.....*Robert D. Bogan*..... by .....  
(COUNTY OFFICIAL) (DEPUTY)