

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

60

History of original corner establishment:

Corner established by Robb and Gradon in 1881 under General Land Office Contract No. 383.

Surveyor General's Records state:

Set stone 14 x 10 x 5 and built stone mound, as per instructions for Cor. to Secs. 21, 22, 27 & 28, From which:

A pine 24" dia. bears N 85° E 132 lks. dist.

A pine 40" dia. bears S 70° E 123 lks. dist.

DIAGRAM

T10S	R33E
S 21	S 22
S 28	S 27
1980	
PLS 848	

Description of corner evidence found:

No evidence found. River has meandered through this area over the past 100 years.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 30" x 3" aluminum monument with 3 1/2" aluminum cap stamped as shown, 25" in the ground and placed a ring of stone around pipe.

From which:

A power pole bears N 83° W, 35.3 ft. scribed T10S R33E S 21 BT.

Nailed a brass washer stamped PLS 848 and bearing tree sign to pole. Painted a red band around pole.

A steel post with warning sign bears N, 4.8 ft.

A steel post with warning sign bears S, 5.0 ft.

Witnesses to above corner:

REGISTERED
PROFESSIONAL
LAND SURVEYOR

D. Brinton

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

P. Negus

Office of..... Co. Surveyor..... County of... Grant
State of..... Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 20 day of Aug, 1980
Robert D. Brinton by _____
(COUNTY OFFICIAL) (DEPUTY)