

34

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established.

DIAGRAM

T10S R33E
NW 1/16
S 30
1980
PLS 848

Description of corner evidence found:

N/A

Description of monument and accessories | established to perpetuate the original location of this corner:

Set 30" x 3" aluminum pipe with 3 1/2" aluminum cap, stamped as shown, 26" in the ground.

From which:

A pine 8" dia. bears N 47° W, 19.6 ft. scribed NW 1/16 S 30 BT.

A pine 9" dia. bears S 40° 15' W, 28.3 ft. scribed NW 1/16 S 30 BT.

Nailed brass washers stamped PLS 848 and bearing tree signs to all bearing trees. Painted red band around all bearing trees.

Set steel fence post 5 ft. West and 5 ft. North with BOUNDARY and LAND SURVEY signs attached.

Witnesses to above corner:

M. Ferguson

S. Hutchison

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Douglas M. Ferguson
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Office of... Co. Surveyor... County of... Grant
State of... Oregon... I hereby certify that the within instrument was filed in this office
for record on the... day of... 1980
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)