

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

(Reference FSH 5681.65)

History of original corner establishment:

Set by Robb and Graden in 1881, under contract #383 dated 3/26/1881.

Set a stone 30"x 18"x 12" in a mound of stone. No Bearing Trees.

DIAGRAM

S.C.
T.10S. R.34E.

S. $\frac{1}{4}$ S.32

T.11S.

Description of corner evidence found:

None.

Description of monument and accessories | established to perpetuate the original location of this corner

Set a 2 $\frac{1}{2}$ " x 30" iron post, 24" in the ground, with brass cap, at proportionate distance from sec. cors. to the East and West.

Marked new Bearing Trees as follows:

a pine 21" diam., bears N.68 E., 316 lks. distant, marked; SC $\frac{1}{4}$, S.32, B.T.

REGISTERED
OREGON
LAND SURVEYOR

JULY 10, 1964
DUANE I. GRIFFITH
644

Cap marked:

S.C.
T.10S. R.34E.

S.32

$\frac{1}{4}$

1967

L.S. 644 ORE.

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office
for record on the day of; 19....., at..... o'clock m., (signed)
..... by
(COUNTY OFFICIAL) (DEPUTY)

SEE REMON FILED
MAY 1, 1964

RECEIVED AND
FILED

JOHN LIVEIRA, County Clerk

By..... Deputy