

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was originally established by Herman D. Gradon under GLO contract No. 416 during October, 1881. Surveyors General's notes state: "Set a quartz stone 20x12x8 ins., 15 ins. in the ground for 1/4 sec. cor. marked 1/4 on W. face; from which a black pine 12 ins. diam. bears S30°E., 14 lks. dist. marked 1/4S BT. A Tamarac 4 ins. diam. bears N45°W., 5 lks. dist. marked 1/4S BT.

Index File No. G-9

DIAGRAM

T10S R35E
1/4

S8 + S9

Description of corner evidence found:

Found 22x12x7 inch stone clearly marked 1/4 on west down side. Tamarac BT, N75°W., 5 links now down. SE BT covered by down Fir.

Description of monument and accessories I established to perpetuate the original location of this corner:

At center of the above stone set 2 1/2" X 30" galvanized pipe and brass cap marked: Set pipe 26" in the ground. Placed monument stone alongside. No rock in the area. From which by magnetic declination of N20°E: A 18" Tamarac bears N70°E., 56.2 ft., scribed 1/4 S9 BT. A 16" Tamarac bears S76°W., 17.3 ft., scribed 1/4 S8 BT. Painted blazes red and 6" red band around. Placed 54-3s, 54-4s and brass washers stamped PLS 1051 on BT. Old BT was signed. Placed 54-4 on steel fence post 5' North of the corner

T10S R35E
1/4
S8 + S9
OR PLS 1051
1981

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland
Troy Phillips

July 9, 1981

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Barry B. Barbour

OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

Office of County Surveyor..... County of Grant
State of Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 20 day of July....., 1981
Robert A. Giffert by
(COUNTY OFFICIAL) (DEPUTY)