


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

None.



Description of corner evidence found:

None.

Description of monument and accessories I established to perpetuate the original location of this corner:

A 2 1/2" by 30" aluminum pipe with 2 1/2" aluminum cap was set 15" in the ground and surrounded with a mound of stone from which:

A 8" spruce bears N23 1/2°E-21.5' scribed C-E 1/16 S 9 BT.

A 6" white fir bears S1 1/2°E-55.5' scribed C-E 1/16 S 9 BT.

Each new bearing tree has a brass washer stamped PLS 1106 nailed to the face of the blaze. Attached sign 54-3 and 54-9 to each bearing tree and painted face of blaze and a 6" red band around each bearing tree.

Set steel fence post East and South of corner on National Forest Boundary and attached sign 54-2 to both posts and sign 54-9 to one post.

Used steel tape and staff compass with 20°E declination, measured to the center of the bearing trees.

This corner was monumented on August 11, 1983.

Witness: Ken Yokom

Cap is marked:

T10S R35E

C-E 1/16

C — . — C

S 9

1983

PLS 1106

Office of County Surveyor Grant

State of Oregon

for record on the 10 day of May, 1984

Robert D. Beyer

(COUNTY OFFICIAL)

by

(DEPUTY)

I hereby certify that the within instrument was filed in this office