

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. P-9

History of original corner establishment:

Corner was originally established by Herman D. Gradon under G.L.O. contract No 416 during October, 1881. Surveyor General's notes state: "Set a basalt stone 16x10x6 ins. 11 ins. in the ground for 1/4 sec. cor. marked 1/4 on west face: from which: A fir 18 ins. diam. bears S20°E, 14 lks. dist marked 1/4S BT. A pine 36 ins. diam. bears S65°W, 30 lks. dist. marked 1/4S BT."

DIAGRAM

T10S R35E
1/4
S20 + S21
OR PLS 1051
1980

Description of corner evidence found:

In nearby rock jack found clearly marked 1/4, 18x11x6 inch stone. Near a small pine found rock hold with old rusty location tag and 2 rotten wood posts. From rock hold a 36" pine stump bears S63°W, 18.9 ft. and rotten stump bears S20°E, 13.5 ft.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the center of the above described point set 2 1/2" X 30" galvanized pipe and brass cap marked: Set pipe 22" in the ground and mound of stone around to cap. Placed marked stone alongside. From which by magnetic declination of N20°E: A 9" lodgepole pine bears N77°E, 48.1 ft. scribed 1/4S21 BT. A 24" pine bears N38°W, 131.8 ft. scribed 1/4S20 BT. Painted blazes red and 6" red band around. Placed 54-3s, 54-4s and brass washers stamped PLS 1051 on BTs. Placed 54-2 and 54-4 on steel fence post 5' south of the corner.

T10S R35E
1/4
S20 + S21
OR PLS 1051
1980

I hereby certify that the above corner monument was reestablished as herein described.

Witnesses: Daniel Rowland
Larry Shirley

August 21, 1980

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Barry B. Barbour

**OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051**

Office of.....County Surveyor.....County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the 20th day of January, 1981.
Robert S. Dagit by
(COUNTY OFFICIAL) (DEPUTY)