

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Index File No. Z-23

History of original corner establishment:

Corner was originally established by Herman D Gradon under G.L.O. contract No. 416 during November, 1880. Surveyor General's notes state: "Set basalt stone 14x14x8 in mound of stone for 1/4 sec. cor. from which a tamarack 18 in. diam. bears N88°E, 38 lks. dist."

DIAGRAM

T10S R35E
1/4 S36
T11S

Description of corner evidence found:

Found set 14x12x8 in. stone marked 1/4 on bottom. (Cup-side down) from which a 24" tamarack with grown over blaze bears N83°E, 22.8 ft.

Description of monument and accessories established to perpetuate the original location of this corner:


At the center of the above described stone set 2 1/2" X 30" galvanized pipe and brass cap marked; Set pipe 25" in the ground and mound of stone at base of pipe.
From which by magnetic declination of N20°E:
A 21" Fir bears N43°W, 70.8 ft. scribed 1/4S36 BT. Painted blazes red and 6" red band around. Placed 54-3, 54-4 and brass washers stamped PLS 1051 on BTs. Old BT is signed. Placed 54-4 in steel fence post 5' East of the corner.

T10S R35E
1/4 S36
T11S
OR PLS 1051
1980

I hereby certify that the above corner monument was reestablished as herein dexcribed.

Witnesses: Robert Boling
Larry Shirley

July 21, 1980



Barry B. Barbour
OREGON
OCT. 17, 1975
BARRY B. BARBOUR
1051

Office of _____ County Surveyor _____ County of _____ Grant
State of _____ Oregon _____, I hereby certify that the within instrument was filed in this office
for record on the 20th day of January, 1981.
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)