H.5-21.5 CS 1107

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
New corner

DIAGRAM
T10S R32E
SWSW1/64
+
S12

Description of corner evidence found:

Description of monument and accessories I establish to perpetuate the original location of this corner:
Set a 2½x30" aluminum monument 22" in the ground in a mound of stone.
A 17" Fir bears S10°33'W 40.3 ft, scribed SWSW1/64S12BT.
A 10" Fir bears N38°34'W 35.0 ft, scribed SWSW1/64S12BT.

T10S R32E
SWSW1/64
+
S12
PLS1918
1989

New BTs have 3/4" brass washers marked PLS1918 attached to the BT blaze, faces and bands painted with red tree marking paint, and BT tags and Land Survey Monument signs. A steel fence post with Land Survey Monument sign is driven approximately 3-5 feet from the corner.

Sun Cadastral Survey, 53-04H1-7-4011
Project No. 8722LC
Field Book: 8-20
Work Accomplished: 9/6/89
Witnesses: Louise Parsons

PARSONS SURVEYING
1915 S.E. Stone Street
Corvallis, OR 97333
(503) 752-7515

REGISTERED
PROFESSIONAL
LAND SURVEYOR
Tyler B Parsons
OREGON
JULY 18, 1980
TYLER B. PARSONS
1918

Office of County Surveyor County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office for record on the 21 day of NOV, 19 89

Robert D Bagett by _____
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

H½-21½